
























































ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
	<b>IP CAMERA</b>		<b>NEW</b>	
1	AWASIS 5000PWL-F-SAF-NF	1/3" 5.0Megapixel Starlight CMOS Sensor H265/H264 Encoding - Dual Stream 3.6mm F1.6 Starlight Advance Fixed lens Main Stream 5MP (2880 * 1620) @ 20fps / 4MP @ 25fps Built in <b>Microphone</b> Digital WDR, 3DNR, HLC, BLC 30m Warmlight, 3 EXIR LED Standard Onvif (Compatible with Dahua, Hikvision, Maxron & etc) Private Protocol With Z Series XVR Human Body Detection IP67 Metal Case, 12VDC, <b>Smart PoE</b> Fara View Mobile Monitoring, VMS Monitoring		17,800,000
	<b>IP CAMERA</b>		<b>NEW</b>	
2	KAVARIA 5000PWL-F-SAF-NF	1/3" 5.0Megapixel Starlight CMOS Sensor H265/H264 Encoding - Dual Stream 3.6mm F1.6 Starlight Advance Fixed lens Main Stream 5MP (2880 * 1620) @ 20fps / 4MP @ 25fps Built in <b>Microphone</b> Digital WDR, 3DNR, HLC, BLC 50m Warmlight, 4 EXIR Power LED Standard Onvif (Compatible with Dahua, Hikvision, Maxron & etc) Private Protocol With Z Series XVR Human Body Detection IP67 Metal Case, 12VDC, <b>Smart PoE</b> Fara View Mobile Monitoring, VMS Monitoring		20,700,000
3	METIS 200ASF-SL	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, High Power LED OSD Menu by UTC (output 4-in-1)		5,950,000
4	DEVRA 200ASF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, High Power LED OSD Menu by UTC (output 4-in-1)		5,850,000
5	DEVRA 200ASF-SLA	HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, 24 SMD LED Built in MIC OSD Menu by UTC (output 4-in-1)		7,050,000
6	DEVRA 200DSF-SA	HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 2.8mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 2 Dual LED Built in MIC OSD Menu by UTC (output 4-in-1)		8,600,000
7	NORMA 200ASF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, 24 LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		7,600,000
8	NORMA 200ASF-SL	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, 24 SMD LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		7,920,000
9	NORMA 200WSF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 2 Exir LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		9,500,000







ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
10	 NORMA 200WSF-SA	 HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 2.8mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 2 Exir LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		10,000,000
11	 NORMA 500WSF-SA	 HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 2.8mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 2 Exir LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		12,900,000
12	 DORIS 200WSF-SA	 HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 2.8mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40m Warmlight Length, 4 Array LED OSD Menu by UTC (output 4-in-1) Built in MIC		8,050,000
13	 LARIS 500DSF-SA	 HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 2.8mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 40m Warmlight - 50m IR Length, 4 Dual LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Ball		13,200,000
14	ARTEMIS 200ASF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC OSD Menu by UTC (output 4-in-1) 40~45m IR Length, 24 SMD LED IP66, Metal Case		8,200,000
15	POLARIS 200ALF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6 mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m IR Length, 6 Mini Array OSD Menu by UTC(output 4-in-1) IP66, Metal Case		7,645,000
16	 NESTOR 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40m Warmlight, 4 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,400,000
17	 NESTOR 500WLF-SA	 HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 40m Warmlight, 4 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		13,400,000
18	 NESTOR 200DLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40m Warmlight - 60m IR Length, 4 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,900,000
19	 NESTOR 500DLF-SA	 HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 40m Warmlight - 60m IR Length, 4 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		13,900,000













ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
20	 HELIX 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length - 3 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		9,800,000
21	 HELIX 200WLF-SA	 HDTVI Camera 1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length - 3 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		10,200,000
22	 HELIX 200DLF-S	1/2.9" Starlight CMOS Sensor, 2.0Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,200,000
23	 AWASIS 200DLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,400,000
24	 AWASIS 500DLF-SA	 HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 30m Warmlight - 40m IR Length, 3 Dual EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		13,400,000
25	 AWASIS 500WLF-SA	 HDTVI Camera 1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 30m Warmlight, 3 EXIR LED OSD Menu by UTC(output 4-in-1) Built in MIC IP66, Metal Case		12,900,000
26	 AWASIS 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 3 Exir LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,000,000
27	 AWASIS 500WLF-S	1/2.5" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 3 EXIR LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		12,000,000
28	 Callisto 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 4 Array LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		9,500,000
29	 Callisto 500WLF-S	1/2.5" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 4 Array LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		11,550,000
30	CAPELLA 200ALF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6 mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 35~40m IR Length, 6 Mini Array OSD Menu by UTC(output 4-in-1) IP66, Metal Case		7,650,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
31	CAPELLA 200ALF-SL	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6 mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 35~40m IR Length, 6 Mini Array OSD Menu by UTC(output 4-in-1) IP66, Metal Case		7,820,000
32	CAPELLA 500ALF-S	1/2.5" Starlight Image Sensor, 5.0 Megapixel 3.6 mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC OSD Menu by UTC(output 4-in-1) 35~40m IR Length, 6 Mini Array IP66, Metal Case		10,950,000
33	ERIS 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 2 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		9,550,000
34	ERINOM 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 25~30m Warmlight Length, 4 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		9,620,000
35	PARSIS 200ALF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30~35m IR Length, 6 Array LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		7,650,000
36	PARSIS 200ALF-SL	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30~35m IR Length, 6 Array LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		7,810,000
37	PARSIS 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 30m Warmlight Length, 6 Array LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		9,140,000
38	PARSIS 500WLF-S	1/2.5" Starlight Image Sensor, 5.0 Megapixel 3.6 mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC OSD Menu by UTC(output 4-in-1) 30m Warmlight Length, 6 Array LED IP66, Metal Case		11,220,000
39	NARSIS 200ALF-EL	1/2.9" CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40~45m IR Length, 8 Array LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		8,530,000
40	NARSIS 200ALF-SL	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 40~45m IR Length, 8 Array LED OSD Menu by UTC (output 4-in-1) IP66, Metal Case		8,800,000
41	NARSIS 500ALF-S	1/2.5" Starlight Image Sensor, 5.0 Megapixel 3.6 mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC OSD Menu by UTC(output 4-in-1) 40~45m IR Length, 8 Array LED IP66, Metal Case		10,900,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
42	AVILON 200ALV-E	1/2.9" CMOS Sensor, 2.0 Megapixel 2.8~12mm Varifocal lens Resolution 1932(H) × 1088(V) DWDR, 3DNR, AWB, BLC 50~60m IR Length OSD Menu by UTC(output 4-in-1) IP66, Metal Case		14,630,000
43	AVILON 500ALV-E	1/2.5" CMOS Sensor, 5.0 Megapixel 2.8~12 mm Varifocal lens Resolution 2608(H) × 1952(V) DWDR, 3DNR, AWB, BLC OSD Menu by UTC(output 4-in-1) 50~60m IR Length IP66, Metal Case		18,810,000
44	NESO 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 60m Warmlight Length, 8 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		11,880,000
45	KAVARIA 200WLF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 50m Warmlight Length, 4 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		11,990,000
46	KAVARIA 500WLF-S	1/2.8" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 2560(H) × 1920(V) DWDR, 3DNR, AWB, BLC 50m Warmlight Length, 4 Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		13,970,000
47	KAVARIA 200ALF-S	1/2.9" Starlight CMOS Sensor, 2.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 1920(H) × 1080(V) DWDR, 3DNR, AWB, BLC 70~80m IR Length , High Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		10,175,000
48	KAVARIA 500ALF-S	1/2.5" Starlight CMOS Sensor, 5.0 Megapixel 3.6mm F1.2 Starlight Fixed lens Resolution 3072(H) × 1728(V), 16:9 DWDR, 3DNR, AWB, BLC 70~80m IR Length , High Power LED OSD Menu by UTC(output 4-in-1) IP66, Metal Case		12,810,000
49	OHD-6104XF-A1	 4CH H.265 5MP-Lite XVR 4CH AHD Camera(HD Mode), 16CH 5MP IP Camera (IP Mode) Preview Capacity: 4*(5MP-Lite@20fps/4MP-Lite@25fps/1080P@25fps) Code Capacity: 4*(5MP-Lite@12fps/4MP-Lite@17fps/1080P@18fps/1080P-Lite@25fps) 4CH Playback Support AOC (Audio Over Coaxial For All Channel) Pentabrid (Analogue,AHD,CVI,TVI,IP) HDMI & VGA Video Output 1 SATA HDD Up to 8TB 1CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod Mobile APP & CMS PC Software		19,900,000
50	OHD-4104ZF-A1	 4CH H.265 1080P-Lite XVR Preview Capacity: 4*1080P-Lite@25fps Code Capacity: 4*1080P-Lite@24fps 2CH Playback Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analogue,AHD,CVI,TVI,IP) HDMI & VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers		18,150,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
51	OHD-6104ZF-A1	<p><b>SMD</b> 4CH AHD H.265 5MP-Lite XVR 4CH AHD Camera + 1CH IP Camera Preview Capacity: 4*5MP-Lite@20fps Code Capacity: 4*(5MP-Lite@12fps/4MP-Lite@17fps/1080P@15fps/1080P-Lite@25fps) 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analogue,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App Adaptive Iran &amp; International Servers</p>		22,500,000
52	OHD-6104ZFN-A1	<p><b>SMD</b> 4CH H.265 5MP-Lite XVR 4CH Camera + 1CH IP Camera Preview Capacity: 4*5MP-Lite@20fps Code Capacity: 4*(5MP-Lite@12fps/4MP-Lite@17fps/1080P@15fps/1080P-Lite@25fps) 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support face detection 1CH (With Special Firmware Upgrade / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analogue,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		22,500,000
53	OHD-8104ZFN-4KL/A4	<p><b>SMD</b> 4CH H.265 <b>Real 5MP</b> XVR 4CH Camera (Analog &amp; IP) Preview Capacity: 4*5MP@12fps Code Capacity: 4*(5MP@12fps/4MP@15fps/1080P@25fps) 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analogue,AHD,CVI,TVI,IP) <b>HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC)</b> 1 SATA HDD Up to 10TB <b>4CH Audio In/1CH Audio Out</b> 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		31,000,000
54	OHD-8104ZF-4KL/A4	<p><b>SMD</b> 4CH H.265 <b>Real 5MP</b> XVR 4CH Camera (Analog &amp; IP) Preview Capacity: 4*5MP@12fps Code Capacity: 4*(5MP@12fps/4MP@15fps/1080P@25fps) 4CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analogue,AHD,CVI,TVI,IP) <b>HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC)</b> 1 SATA HDD Up to 10TB <b>4CH Audio In/1CH Audio Out</b> 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		31,000,000
55	OHD-6104XH-A1	<p>4CH H.265 5MP-Lite XVR 4CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:4*(5MP-Lite@20fps/4MP-Lite@25fps/1080P@25fps) Code Capacity: 4*(5MP-Lite@8fps/4MP-Lite@15fps/1080P@18fps/1080P-Lite@25fps) 4CH Playback Support real-time face detection, Face list, Face playback Pentabrid (Analogue,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 6TB 1CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>		22,500,000
56	OHD-6108XF-A1	<p>8CH H.265 5MP-Lite XVR 8CH AHD Camera(HD Mode), 16CH 5MP IP Camera (IP Mode) Preview Capacity: 8*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps) Code Capacity: 8*(5MP-Lite@5fps/4MP-Lite@8fps/1080P-Lite@15fps) 8CH Playback Support AOC (Audio Over Coaxial For All Channel) Pentabrid (Analogue,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 8TB 1CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4 IOS-Andriod Mobile APP &amp; CMS PC Software</p>		25,000,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
57	OHD-6108ZF-A1	<p><b>SMD</b> 8CH AHD H.265 5MP-Lite XVR 8CH AHD Camera + 2CH IP Camera Preview Capacity: 8*5MP-Lite@12fps Code Capacity: 8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps) 8CH Playback Support SMD (Human/Vehicle Classification For 4CH) Support face detection 1CH (With Special Firmware Upgarde / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1CH Audio In / 1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App Adaptive Iran &amp; International Servers</p>		28,500,000
58	OHD-6108ZFN-A1	<p><b>SMD</b> 8CH H.265 5MP-Lite XVR 8CH Camera + 2CH IP Camera Preview Capacity: 8*5MP-Lite@12fps Code Capacity: 8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps) 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support face detection 1CH (With Special Firmware Upgarde / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		28,500,000
59	OHD-8108ZFN-4KL/A4	<p><b>SMD</b> 8CH H.265 4K-Lite &amp; Real 5MP XVR 8CH Camera + 2CH IP Preview Capacity: 8*(4K-Lite@15fps/5MP@12fps) Code Capacity: 8*(4K-Lite@9fps/5MP@8fps/4MP@10fps/1080P@20fps) 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support face detection 1CH (With Special Firmware Upgarde / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		45,500,000
60	OHD-8208ZF-4KL/A4	<p><b>SMD</b> 8CH H.265 4K-Lite &amp; Real 5MP XVR 8CH Camera + 2CH IP Preview Capacity: 8*(4K-Lite@15fps/5MP@12fps) Code Capacity: 8*(4K-Lite@9fps/5MP@8fps/4MP@10fps/1080P@20fps) 8CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support face detection 1CH (With Special Firmware Upgarde / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC) 2 SATA HDD Up to 10TB For each port (Change Adaptur to 12V/5A) 4CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran &amp; International Servers</p>		45,500,000
61	OHD-6108XH-A1	<p>8CH AHD H.265 5MP-Lite XVR 8CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:8*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps) Code Capacity:8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P@8fps/1080P-Lite@15fps) 8CH Playback:4ch main stream/8ch sub-stream Support real-time face detection, Face list, Face playback Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 6TB 1CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>		28,800,000
62	OHD-6108XH-A4	<p>8CH AHD H.265 5MP-Lite XVR 8CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:8*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps) Code Capacity:8*(5MP-Lite@6fps/4MP-Lite@8fps/1080P@8fps/1080P-Lite@15fps) 8CH Playback:4ch main stream/8ch sub-stream Support real-time face detection, Face list, Face playback Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 1 SATA HDD Up to 6TB 4CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>		29,200,000

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
63	OHD-6216ZF-A1	<p><b>SMD</b>  </p> <p>16CH AHD H.265 5MP-Lite XVR 16CH AHD Camera + 4CH IP Camera Preview Capacity:16*5MP-Lite@12fps Code Capacity:16*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps) 16CH Playback Support SMD (Human/Vehicle Classification For 8CH) Support face detection 1CH (With Special Firmware Upgarde / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 2 SATA HDD Up to 10TB for each port 1CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod FARA VIEW App Adaptive Iran &amp; International Servers</p>		49,500,000
64	OHD-6116ZFN-A1	<p><b>SMD</b>  </p> <p>16CH H.265 5MP-Lite XVR 16CH Camera + 4CH IP Camera Preview Capacity:16*5MP-Lite@12fps Code Capacity:16*(5MP-Lite@6fps/4MP-Lite@8fps/1080P-Lite@16fps) 16CH Playback Support SMD (Human/Vehicle Classification For 16CH) Support face detection 1CH (With Special Firmware Upgarde / Not At The Same Time As SMD) Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Simultaneous Output 1 SATA HDD Up to 10TB 1CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		48,800,000
65	OHD-8116ZHN-4KL/A4	<p><b>SMD</b>  </p> <p><b>HISILICON</b> NEW AI Chipset</p> <p>16CH H.265 4K-Lite &amp; Real 5MP XVR 16CH Camera (Analog &amp; IP) Preview Capacity: 16*(4K-Lite@15fps/5MP@12fps) Code Capacity: 16*(4K-Lite@7fps/5MP@8fps) 16CH Playback Support SMD (Human/Vehicle Classification For 16CH) Support 1CH face detection Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio) Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI 4K &amp; VGA Video Simultaneous Output - Analog Video Output (BNC) 1 SATA HDD Up to 10TB 4CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran &amp; International Servers</p>		69,000,000
66	OHD-6216XH-A4	<p>16CH H.265 5MP-Lite XVR 16CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity:16*(5MP-Lite@12fps/4MP-Lite@15fps/1080P-Lite@25fps) Code Capacity:16*(5MP-Lite@6fps/4MP-Lite@8fps/1080P@8fps/1080P-Lite@15fps) 16CH Playback Support real-time face detection, Face list and Face playback Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 2 SATA HDD Up to 6TB for each port 4CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software</p>		49,500,000
67	OHD-8216X-A2	<p><b>AI</b> </p> <p>16CH H.265 8MP-Lite XVR 16CH AHD Camera(HD Mode), 16CH IP Camera (IP Mode) Preview Capacity: 16*(8MP-Lite@15fps/5MP@12fps/5MP-Lite@20fps/4MP@15fps/3MP@18fps/4MP-Lite/3MP-Lite/1080P/720P@25fps) Code Capacity: 16*(8MP-Lite@8fps/5MP@6fps/5MP-Lite@12fps/4MP@8fps/3MP@10fps/3MP-Lite@18fps/4MP-Lite/1080P@15fps/720P@25fp) 16CH Playback Support real-time face detection, Face list and Face playback AI Functions: Intrusion , Line crossing Support Phone push on Mobile app Pentabrid (Analoge,AHD,CVI,TVI,IP) HDMI &amp; VGA Video Output 2 SATA HDD Up to 6TB for each port 2CH Audio In/1CH Audio Out 2*USB 2.0, 1*10/100 Mbps LAN Interface P2P support, IOS-Andriod Mobile APP &amp; CMS PC Software Wireless Mouse</p>		68,000,000